

Installation Instructions



AerialShields®

Open Camera
Scan Code

▶ Watch Install



1. Install AerialShields in accordance with manufacturer's instructions. **For interior use only.**
2. Ensure platform is free of all tools/debris and extend platform to desired length.
3. Take AerialShield and removable door out of the package. Set the removable door with the yellow caution strip aside. Do not unfold the AerialShield.
4. With the folded AerialShield, enter the lift. Starting at the platform end furthest from the entry, lay the folded AerialShield on the platform floor with the black base down. Unroll toward the entry point with the black base laying flat along the length of the platform.
5. Lift the left and right sides of the AerialShield and step onto the black platform base.
6. Separate velcro on the AerialShield and stretch the bungee over the bar above the entry point. Stretch the bungee down about 6-8"
7. Stretch the bungee over the sides and the other end of the basket.
8. Exit the machine and pull bungee down around the platform base.
9. Straighten and close velcro around entry.
10. Separate the velcro strip on the removable door and center over the entry point with yellow caution at top.
11. Close the velcro strip on the removable door.

Questions? Call Us 1.888.SOCK.911

WARNING

The machine should always be OFF with the key removed during each step of the installation and removal of this product.

Installation Instructions



1. Install AerialShields in accordance with manufacturer's instructions. **For interior use only.**
2. Ensure platform is free of all tools/debris and extend platform to desired length.
3. Take AerialShield and removable door out of the package. Set the removable door with the yellow caution strip aside. Do not unfold the AerialShield.
4. With the folded AerialShield, enter the lift. Starting at the platform end furthest from the entry, lay the folded AerialShield on the platform floor with the black base down. Unroll toward the entry point with the black base laying flat along the length of the platform.
5. Lift the left and right sides of the AerialShield and step onto the black platform base.
6. Separate velcro on the AerialShield and stretch the bungee over the bar above the entry point. Stretch the bungee down about 6-8"
7. Stretch the bungee over the sides and the other end of the basket.
8. Exit the machine and pull bungee down around the platform base.
9. Straighten and close velcro around entry.
10. Separate the velcro strip on the removable door and center over the entry point with yellow caution at top.
11. Close the velcro strip on the removable door.

Questions? Call Us 1.888.SOCK.911

WARNING

The machine should always be OFF with the key removed during each step of the installation and removal of this product.